

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 17/11/2022 Revision date: 17/06/2021 Version: 5.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Air Intake & Carburettor Cleaner (Aerosol)

Product code : W54179 Type of product : Detergent Vaporizer : Aerosol Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Cleaning product

Maintenance product

Function or use category : Aerosol propellants

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Distributor Supplier

ITW ADDITIVES INTL B.V. Wynn Oil U.K. (ITW Additives UK)

Industriepark-West 46 7 Westwood House, Westwood Business Park, Coventry

9100 Sint-Niklaas CV4 8HS West Midlands UK

Belgium

T +32 3 766 60 20 - F +32 3 778 16 56 T +44 (0)24 7647 4069

msds@wynns.eu - www.wynns.com helpline@wynns.uk.com - http://www.wynns.uk.com

1.4. Emergency telephone number

: BIG: +32(0)14 58 45 45 (NL FR EN DE) **Emergency number**

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229 Acute toxicity (dermal), Category 4 H312 Acute toxicity (inhalation:gas) Category 4 H332 Skin corrosion/irritation, Category 2 H315 Serious eye damage/eye irritation, Category 2 H319 Specific target organ toxicity - Single exposure, Category 3, Respiratory H335

tract irritation

H373 Specific target organ toxicity – Repeated exposure, Category 2

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02





GHS07

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Signal word (CLP) : Danger

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated. H312+H332 - Harmful in contact with skin or if inhaled.

H315 - Causes skin irritation.H319 - Causes serious eye irritation.H335 - May cause respiratory irritation.

H373 - May cause damage to organs (hearing organs) through prolonged or repeated

exposure (if inhaled, oral).

Precautionary statements (CLP) : P261 - Avoid breathing vapours, spray.

P280 - Wear protective gloves, protective clothing, eye protection.

P271 - Use only outdoors or in a well-ventilated area.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction mass of ethylbenzene and xylene	EC-No.: 905-588-0 REACH-no: 01-2119488216- 32	≥ 50	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Hydrocarbons, C3-4-rich, petroleum distillate	CAS-No.: 68512-91-4 EC-No.: 270-990-9 REACH-no: 01-2119485926- 20	10 – 25	Flam. Gas 1A, H220
Acetone substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-	10 – 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
2-butoxyethanol substance with a Community workplace exposure limit	CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0 REACH-no: 01-2119475108- 36	2,5 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
reaction mass of ethylbenzene and xylene	EC-No.: 905-588-0 REACH-no: 01-2119488216- 32	(10 ≤C < 100) STOT RE 2, H373

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Check the vital functions. Keep victim at rest in half upright position. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Keep watching the victim. Give psychological aid. Prevent cooling by covering the victim (no warming up). Keep the victim calm, avoid physical strain. If necessary seek medical advice.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	 After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: If swallowed, rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. As it is a spray can packaging it is most unlikely that large quantities will be swallowed.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Nausea. May cause respiratory irritation.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking. Harmful in contact with skin. Causes skin irritation. Swelling of the skin. Red skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	Risk of aspiration pneumonia. Risk of lung oedema.
Chronic symptoms	: Overexposure to vapours may cause headache.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. AFFF foam. ABC-powder. Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol. Heating may cause a fire or explosion.

Explosion hazard : No direct explosion hazard. Contains gas under pressure; may explode if heated. Heat may

build pressure, rupturing closed containers, spreading fire and increasing risk of burns and

injuries.

Reactivity in case of fire : Upon combustion: CO and CO2 are formed.

17/06/2021 (Revision date) EN (English) 3/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

Firefighting instructions : Cool closed containers exposed to fire with water spray. Fight fire from safe distance and

protected location.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable gloves and eye/face protection. Wear suitable respiratory equipment in case

of insufficient ventilation. protective clothing.

Emergency procedures : Mark the danger area. Stop engines and no smoking. Keep upwind. Prevent flow to low

areas. No flames, no sparks. Eliminate all sources of ignition. Wash contaminated clothes.

6.1.2. For emergency responders

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Do not allow product to spread into the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain the spilled material by bunding. Collect spillage.

Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel

into container for disposal. Clean preferably with a detergent - Avoid the use of solvents.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Do not pierce or burn, even after use. Not expected to present a significant hazard under

anticipated conditions of normal use.

Precautions for safe handling : Meet the legal requirements. Avoid contact with skin and eyes. Take precautionary

measures against static discharge. Provide good ventilation in process area to prevent formation of vapour. Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

Hygiene measures : Use good personal hygiene practices. IF ON SKIN: Wash with plenty of water/.... Wash

contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep in fireproof place. Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

Storage temperature : ≤ 45 °C

Heat and ignition sources : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Information on mixed storage : Store separately.

Storage area : Meet the legal requirements. Fireproof storeroom. Ventilation along the floor.

Special rules on packaging : Meet the legal requirements. Labelling according to.

Packaging materials : Aerosol.

7.3. Specific end use(s)

See product bulletin for detailed information.

17/06/2021 (Revision date) EN (English) 4/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA [ppm] 500 ppm Belgium - Occupational Exposure Limits OEL TWA [ppm] 500 ppm CEL TWA 1210 mg/m² OEL TWA 1210 mg/m² OEL TWA 1210 mg/m² OEL STEL [ppm] 500 ppm CEL STEL [ppm] 1000 ppm Hungary - Occupational Exposure Limits XK (OEL TWA) 1210 mg/m² CK (OEL STEL) 2420 mg/m² KK (OEL TWA) 1210 mg/m² CK (OEL STEL) 2420 mg/m² KK (OEL TWA) 1210 mg/m² CK (OEL STEL) 2420 mg/m² TGG-8u (OEL TWA) 1210 mg/m² TGG-8u (OEL TWA) [ppm] 510 ppm TGG-15min (OEL STEL) 2420 mg/m² TGG-15min (OEL STEL) 1000 ppm 2-butoxyethanol (111-76-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name 2-Butoxyethanol (111-76-2) EU - Indicative Occupational Exposure Limit (IOEL) LOCAL TWA [ppm] 50 ppm IOEL TWA [ppm] 60 ppm OEL TWA [ppm] 60 ppm OEL TWA [ppm] 70 ppm OEL STEL [ppm] 70 ppm OEL TWA [ppm] 70 ppm OEL STEL [ppm] 70 ppm OEL STEL [ppm] 70 ppm OEL STEL [ppm] 70 ppm OEL TWA [ppm] 70 ppm OEL STEL [ppm] 70 ppm			
IOEL TWA 1210 mg/m² IOEL TWA [ppm] 500 ppm Belgium - Occupational Exposure Limits CEL TWA OEL TWA [ppm] 500 ppm OEL STEL 2420 mg/m² OEL STEL [ppm] 1000 ppm Hungary - Occupational Exposure Limits AK (OEL TWA) Note of the Michael Exposure Limits XK (OEL TWA) Note of the Michael Exposure Limits TGG-8u (OEL TWA) [ppm] 1210 mg/m² TGG-9u (OEL TWA) [ppm] 510 ppm TGG-15min (OEL STEL) [ppm] 1020 ppm TGG-15min (OEL STEL) [ppm] 95 mg/m² GCL TWA [ppm] 20 ppm GCL TWA [ppm] 20 ppm GCL STEL [ppm] 50 ppm Regulatory reference 28utoxyethanol # 2-8utoxy-ethanol	Acetone (67-64-1)		
OEL TWA [ppm] 500 ppm DEL TWA 1210 mg/m³ OEL TWA [ppm] 500 ppm OEL STEL [ppm] 1000 ppm DEL STEL [ppm] 1000 ppm Hungary - Occupational Exposure Limits AK (OEL TWA) 1210 mg/m³ CK (OEL STEL) 2420 mg/m³ Netterlands - Occupational Exposure Limits TGG-8u (OEL TWA) [ppm] 510 ppm TGG-8u (OEL TWA) [ppm] 510 ppm TGG-9 (DEL TWA) [ppm] 1900 ppm TGG-9 (DEL TWA) [ppm] 1900 ppm TGG-9 (DEL TWA) [ppm] 1900 ppm TGG-9 (DEL TWA) [ppm] 90 ppm TGG-9 (DEL TWA) [ppm] 90 ppm TGG-9 (DEL STEL) [ppm] 90 mg/m² DGL TWA [ppm] 90 ppm OGEL TWA [ppm] 90 ppm OGEL TWA [ppm] 90 ppm OGE STEL [ppm] 80 ppm Regulatory reference PS-Butoxy-ethanol DGL TWA [ppm] 90 ppm	EU - Indicative Occupational Exposure Limit (IOEL)		
Belgium - Occupational Exposure Limits OEL TWA 1210 mg/m³ OEL TWA [ppm] 500 ppm OEL STEL 2420 mg/m³ OEL STEL [ppm] 1000 ppm Hungary - Occupational Exposure Limits ************************************	IOEL TWA	1210 mg/m³	
OEL TWA 1210 mg/m³ OEL TWA [ppm] 500 ppm OEL STEL 2420 mg/m³ OEL STEL [ppm] 1000 ppm Hungary - Occupational Exposure Limits ***********************************	IOEL TWA [ppm]	500 ppm	
OEL TWA [ppm] 500 ppm OEL STEL [ppm] 4240 mg/m³ OEL STEL [ppm] 1000 ppm Hungary - Occupational Exposure Limits AK (OEL TWA) 1210 mg/m³ CK (OEL STEL) 2400 mg/m³ Netterlands - Occupational Exposure Limits TGG-8u (OEL TWA) 1210 mg/m³ GG-8u (OEL TWA) [ppm] 510 ppm TGG-15min (OEL STEL) 2420 mg/m³ TGG-15min (OEL STEL) [ppm] 1020 ppm Z-butoxyethanol (111-76-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name 2-Butoxyethanol OEL TWA [ppm] 20 ppm OEL TWA [ppm] 50 ppm Remark 246 mg/m³ OEL STEL [ppm] 50 ppm Remark Skin Regulatory reference 2-Butoxyethanol #2-Butoxy-ethanol OEL TWA [ppm] 20 ppm OEL TWA [ppm] 20 ppm OEL TWA [ppm] 20 ppm OEL STEL [ppm] 30 ppm OEL STEL [ppm]	Belgium - Occupational Exposure Limits		
OEL STEL 2420 mg/m³ OEL STEL [ppm] 1000 ppm Hungary - Occupational Exposure Limits AK (OEL TWA) 1210 mg/m³ CK (OEL STEL) 2420 mg/m³ Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 1210 mg/m³ 1210 mg/m³ TGG-15min (OEL STEL) 2420 mg/m³ TGG-15min (OEL STEL) [ppm] 1020 ppm 2-butoxyethanol (111-76-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name 2-Butoxyethanol IOEL TWA 98 mg/m³ IOEL TWA [ppm] 20 ppm IOEL STEL 246 mg/m³ IOEL STEL [ppm] 50 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyéthanol # 2-Butoxy-ethanol OEL TWA 98 mg/m³ OEL TWA [ppm] 20 ppm OEL TWA [ppm] 20 ppm OEL TWA [ppm] 20 ppm OEL STEL [ppm]	OEL TWA	1210 mg/m³	
OEL STEL (ppm] 1000 ppm Hungary - Occupational Exposure Limits AK (OEL TWA) 1210 mg/m² CK (OEL STEL) 2420 mg/m³ Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 1210 mg/m² TGG-8u (OEL TWA) (ppm] 510 ppm GG-15min (OEL STEL) GG-15min (OEL STEL) (ppm) 2420 mg/m² CB-butoxyethanol (111-76-2) EU - Indicativo Occupational Exposure Limit (IOEL) Local name 2-Butoxyethanol IOEL TWA 98 mg/m² IOEL TWA (ppm] 20 ppm IOEL STEL 246 mg/m² IOEL STEL (ppm] 50 ppm Remark Skin Regulatory reference CoMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyéthanol # 2-Butoxy-ethanol OEL TWA 9 mg/m³ OEL TWA (ppm] 20 ppm OEL TWA (ppm] 20 ppm OEL STEL (ppm] 50 ppm Regulatory reference Koninklijk beslui	OEL TWA [ppm]	500 ppm	
Hungary - Occupational Exposure Limits AK (OEL TWA) 1210 mg/m³ CK (OEL STEL) 2420 mg/m³ Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 1210 mg/m³ TGG-8u (OEL TWA) [ppm] 510 ppm TGG-15min (OEL STEL) 2420 mg/m³ TGG-15min (OEL STEL) [ppm] 1020 ppm 2-butoxyethanol (111-76-2) EU - Indicative Occupational Exposure Limit (IOEL TWA) Local name 2-Butoxyethanol IOEL TWA 98 mg/m³ IOEL TWA [ppm] 20 ppm IOEL STEL [ppm] 50 ppm Remark 8kin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyethanol # 2-Butoxy-ethanol OEL TWA 98 mg/m³ OEL TWA 96 mg/m³ OEL TWA 97 mg OEL TWA 96 mg/m³ OEL TWA 96 mg/m³ OEL TWA [ppm] 20 ppm OEL TWA [ppm] 20 ppm OEL STEL [ppm] <td>OEL STEL</td> <td>2420 mg/m³</td>	OEL STEL	2420 mg/m³	
AK (OEL TWA) 1210 mg/m² CK (OEL STEL) 2420 mg/m² Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 1210 mg/m² TGG-8u (OEL TWA) [ppm] 510 ppm TGG-15min (OEL STEL) 2420 mg/m³ TGG-15min (OEL STEL) [ppm] 1020 ppm 2-butoxyethanol (111-76-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name 2-Butoxyethanol IOEL TWA 98 mg/m³ IOEL TWA [ppm] 20 ppm IOEL STEL [ppm] 50 ppm Remark 246 mg/m³ Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyethanol # 2-Butoxy-ethanol OEL TWA 98 mg/m³ OEL TWA 99 mg/m³ OEL TWA 95 mg/m³ OEL TWA [ppm] 20 ppm OEL STEL [ppm] 50 p	OEL STEL [ppm]	1000 ppm	
CK (OEL STEL) 2420 mg/m² Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 1210 mg/m² TGG-8u (OEL TWA) (ppm] 510 ppm TGG-15min (OEL STEL) 2420 mg/m² TGG-15min (OEL STEL) (ppm) 1020 ppm 2-butoxyethanol (111-76-2) EU - Indicative Occupational Exposure Limit (IOEL*) Local name 2-Butoxyethanol IOEL TWA 98 mg/m² IOEL TWA (ppm] 20 ppm IOEL STEL 246 mg/m² IOEL STEL (ppm) 50 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Betjum - Occupational Exposure Limits Local name 2-Butoxyethanol # 2-Butoxy-ethanol OEL TWA 98 mg/m³ OEL TWA (ppm] 20 ppm OEL TWA (ppm] 20 ppm OEL STEL 246 mg/m³ OEL STEL (ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³ </td <td>Hungary - Occupational Exposure Limits</td> <td></td>	Hungary - Occupational Exposure Limits		
Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 1210 mg/m² TGG-8u (OEL TWA) [ppm] 510 ppm TGG-15min (OEL STEL) 2420 mg/m² Count of Common (OEL STEL) [ppm] 1020 ppm 2-butoxyethanol (111-76-2) EU - Indicative Occupational Exposure Limit (IOEL*) Local name 2-Butoxyethanol IOEL TWA 98 mg/m² IOEL TWA [ppm] 20 ppm IOEL STEL [ppm] 50 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyethanol # 2-Butoxy-ethanol OEL TWA 98 mg/m² OEL TWA [ppm] 20 ppm OEL TWA [ppm] 20 ppm OEL STEL 246 mg/m² OEL STEL [ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrété royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m²	AK (OEL TWA)	1210 mg/m³	
TGG-9u (OEL TWA) 1210 mg/m³ TGG-9u (OEL TWA) [ppm] 510 ppm TGG-15min (OEL STEL) 2420 mg/m³ TGG-15min (OEL STEL) [ppm] 1020 ppm 2-butoxyethanol (111-76-2) EU - Indicative Occupational Exposure Limit (IOEL*) Local name 2-Butoxyethanol IOEL TWA 98 mg/m³ IOEL TWA [ppm] 20 ppm IOEL STEL [ppm] 50 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Cols Iname OEL TWA 98 mg/m³ OEL TWA [ppm] 20 ppm OEL TWA [ppm] 20 ppm OEL TWA [ppm] 20 ppm OEL TWA [ppm] 50 ppm OEL STEL 246 mg/m³ OEL STEL [ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrété royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	CK (OEL STEL)	2420 mg/m³	
TGG-8u (OEL TWA) [ppm] 510 ppm TGG-15min (OEL STEL) 2420 mg/m³ TGG-15min (OEL STEL) [ppm] 1020 ppm 2-butoxyethanol (111-76-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name 2-Butoxyethanol IOEL TWA 98 mg/m³ IOEL TWA [ppm] 20 ppm IOEL STEL [ppm] 50 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyéthanol # 2-Butoxy-ethanol OEL TWA 98 mg/m³ OEL TWA [ppm] 20 ppm OEL TWA [ppm] 20 ppm OEL STEL 246 mg/m³ OEL STEL [ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrété royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	Netherlands - Occupational Exposure Limits		
TGG-15min (OEL STEL) 2420 mg/m² TGG-15min (OEL STEL) [ppm] 1020 ppm 2-butoxyethanol (111-76-2) EU-Indicative Occupational Exposure Limit (IOEL) Local name 2-Butoxyethanol IOEL TWA 98 mg/m³ IOEL TWA [ppm] 20 ppm IOEL STEL 246 mg/m³ IOEL STEL [ppm] 50 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyéthanol # 2-Butoxy-ethanol OEL TWA 98 mg/m³ OEL TWA [ppm] 20 ppm OEL TWA [ppm] 20 ppm OEL STEL 246 mg/m³ OEL STEL [ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrèté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	TGG-8u (OEL TWA)	1210 mg/m³	
TGG-15min (OEL STEL) [ppm] 1020 ppm 2-butoxyethanol (111-76-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name 2-Butoxyethanol 1020 ppm IOEL TWA (ppm] 20 ppm IOEL STEL 246 mg/m³ IOEL STEL 500 ppm Remark Skin	TGG-8u (OEL TWA) [ppm]	510 ppm	
2-butoxyethanol (111-76-2) EU - Indicative Occupational Exposure Limit (IOEL) Local name 2-Butoxyethanol IOEL TWA 98 mg/m³ IOEL TWA (ppm] 20 ppm IOEL STEL 246 mg/m³ IOEL STEL [ppm] 50 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyéthanol # 2-Butoxy-ethanol OEL TWA (ppm] 20 ppm OEL TWA 98 mg/m³ OEL TWA (ppm] 20 ppm OEL STEL (ppm] 50 ppm CEL STEL (ppm] 50 ppm OEL STEL (ppm] 60 ppm OEL STEL (ppm] 70 ppm OEL STEL (ppm) 80 ppm Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	TGG-15min (OEL STEL)	2420 mg/m³	
EU - Indicative Occupational Exposure Limit (IOEL)Local name2-ButoxyethanolIOEL TWA98 mg/m³IOEL TWA [ppm]20 ppmIOEL STEL246 mg/m³IOEL STEL [ppm]50 ppmRemarkSkinRegulatory referenceCOMMISSION DIRECTIVE 2000/39/ECBelgium - Occupational Exposure LimitsLocal name2-Butoxyéthanol # 2-Butoxy-ethanolOEL TWA98 mg/m³OEL TWA [ppm]20 ppmOEL STEL246 mg/m³OEL STEL246 mg/m³QEL STEL [ppm]50 ppmRegulatory referenceKoninklijk besluit/Arrété royal 11/03/2002France - Occupational Exposure LimitsVME (OEL TWA)49 mg/m³	TGG-15min (OEL STEL) [ppm]	1020 ppm	
Local name2-ButoxyethanolIOEL TWA98 mg/m³IOEL TWA [ppm]20 ppmIOEL STEL246 mg/m³IOEL STEL [ppm]50 ppmRemarkSkinRegulatory referenceCOMMISSION DIRECTIVE 2000/39/ECBelgium - Occupational Exposure LimitsLocal name2-Butoxyéthanol # 2-Butoxy-ethanolOEL TWA98 mg/m³OEL TWA [ppm]20 ppmOEL STEL246 mg/m³OEL STEL [ppm]50 ppmRegulatory referenceKoninklijk besluit/Arrêté royal 11/03/2002France - Occupational Exposure LimitsVME (OEL TWA)49 mg/m³	2-butoxyethanol (111-76-2)		
IOEL TWA 98 mg/m³ IOEL TWA [ppm] 20 ppm IOEL STEL 246 mg/m³ IOEL STEL [ppm] 50 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyéthanol # 2-Butoxy-ethanol OEL TWA 98 mg/m³ OEL TWA [ppm] 20 ppm OEL STEL 246 mg/m³ OEL STEL [ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA [ppm] 20 ppm IOEL STEL 246 mg/m³ IOEL STEL [ppm] 50 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyéthanol # 2-Butoxyethanol OEL TWA [ppm] 98 mg/m³ OEL TWA [ppm] 20 ppm OEL STEL 246 mg/m³ OEL STEL [ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	Local name	2-Butoxyethanol	
IOEL STEL IOEL STEL [ppm] S0 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyéthanol # 2-Butoxy-ethanol OEL TWA 98 mg/m³ OEL TWA [ppm] 20 ppm OEL STEL OEL STEL 246 mg/m³ OEL STEL DEL STEL DEL STEL STEL STEL STEL STEL STEL STEL STEL	IOEL TWA	98 mg/m³	
IOEL STEL [ppm] 50 ppm Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyéthanol # 2-Butoxy-ethanol OEL TWA 98 mg/m³ OEL TWA [ppm] 20 ppm OEL STEL 246 mg/m³ OEL STEL 246 mg/m³ OEL STEL 50 ppm Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	IOEL TWA [ppm]	20 ppm	
Remark Skin Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyéthanol # 2-Butoxy-ethanol OEL TWA 98 mg/m³ OEL TWA [ppm] 20 ppm OEL STEL 246 mg/m³ OEL STEL [ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	IOEL STEL	246 mg/m³	
Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Belgium - Occupational Exposure Limits Local name 2-Butoxyéthanol # 2-Butoxy-ethanol OEL TWA 98 mg/m³ OEL TWA [ppm] 20 ppm OEL STEL 246 mg/m³ OEL STEL [ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	IOEL STEL [ppm]	50 ppm	
Belgium - Occupational Exposure Limits Local name 2-Butoxyéthanol # 2-Butoxy-ethanol OEL TWA 98 mg/m³ OEL TWA [ppm] 20 ppm OEL STEL 246 mg/m³ OEL STEL [ppm] Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	Remark	Skin	
Local name 2-Butoxyéthanol # 2-Butoxy-ethanol OEL TWA 98 mg/m³ OEL TWA [ppm] 20 ppm 246 mg/m³ OEL STEL OEL STEL [ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
OEL TWA [ppm] 20 ppm OEL STEL 246 mg/m³ OEL STEL [ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	Belgium - Occupational Exposure Limits		
OEL TWA [ppm] 20 ppm OEL STEL 246 mg/m³ OEL STEL [ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	Local name	2-Butoxyéthanol # 2-Butoxy-ethanol	
OEL STEL OEL STEL [ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	OEL TWA	98 mg/m³	
OEL STEL [ppm] 50 ppm Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	OEL TWA [ppm]	20 ppm	
Regulatory reference Koninklijk besluit/Arrêté royal 11/03/2002 France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	OEL STEL	246 mg/m³	
France - Occupational Exposure Limits VME (OEL TWA) 49 mg/m³	OEL STEL [ppm]	50 ppm	
VME (OEL TWA) 49 mg/m³	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002	
	France - Occupational Exposure Limits		
VME (OEL TWA) [ppm] 10 ppm	VME (OEL TWA)	49 mg/m³	
	VME (OEL TWA) [ppm]	10 ppm	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-butoxyethanol (111-76-2)		
VLE (OEL C/STEL)	246 mg/m³	
VLE (OEL C/STEL) [ppm]	50 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	98 mg/m³	
CK (OEL STEL)	246 mg/m³	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	100 mg/m³	
TGG-8u (OEL TWA) [ppm]	20 ppm	
TGG-15min (OEL STEL)	246 mg/m³	
TGG-15min (OEL STEL) [ppm]	50 ppm	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

8.1.4. DNEL and PNEC		
Acetone (67-64-1)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	2420 mg/m³	
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	1210 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	62 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	200 mg/m³	
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	10,6 mg/l	
PNEC aqua (marine water)	1,06 mg/l	
PNEC aqua (intermittent, freshwater)	21 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	30,4 mg/kg dwt	
PNEC sediment (marine water)	3,04 mg/kg dwt	
PNEC (Soil)		
PNEC soil	29,5 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	
2-butoxyethanol (111-76-2)		
DNEL/DMEL (Workers)		
Acute - systemic effects, dermal	89 mg/kg bodyweight/day	
Acute - systemic effects, inhalation	1091 mg/m³	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-butoxyethanol (111-76-2)		
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	98 mg/m³	
Long-term - local effects, inhalation	246 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, dermal	89 mg/kg bodyweight	
Acute - systemic effects, inhalation	426 mg/m³	
Acute - systemic effects, oral	26,7 mg/kg bodyweight	
Long-term - systemic effects,oral	6,3 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	59 mg/m³	
Long-term - systemic effects, dermal	75 mg/kg bodyweight/day	
Long-term - local effects, inhalation	147 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	8,8 mg/l	
PNEC aqua (marine water)	0,88 mg/l	
PNEC aqua (intermittent, freshwater)	9,1 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	34,6 mg/kg dwt	
PNEC sediment (marine water)	3,46 mg/kg dwt	
PNEC (Soil)		
PNEC soil	2,33 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	463 mg/l	

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Vapours are heavier than air and may spread along floors. Provide local exhaust or general room ventilation. Does not require any specific or particular technical measures.

8.2.2. Personal protection equipment

Personal protective equipment:

 $\label{eq:continuous} \mbox{Protective clothing. Gloves. Safety glasses.}$

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.2. Skin protection

Hand protection:

Polyvinylalcohol (PVA). Nitrile rubber. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer

8.2.2.3. Respiratory protection

No additional information available

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Breakthrough time: >30'. Thickness of the glove material >0.1 mm.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Not available Appearance Aerosol Odour characteristic. Odour threshold : Not available Melting point Not available Freezing point : Not available : 56,5 - 173 °C Boiling point Flammability Not available **Explosive limits** Not available Not available Lower explosion limit Upper explosion limit Not available : < 0 °C Flash point Auto-ignition temperature : Not available Decomposition temperature : Not available : Not available рΗ Viscosity, kinematic : Not available Solubility : Partially soluble. Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : 856,5 kg/m³ @ 20 °C Relative density : Not available : Not available Relative vapour density at 20°C Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 100

9.2.2. Other safety characteristics

Additional information : Physical and chemical properties of the active product without gas. The physical and

chemical data in this section are typical values for this product and are not intended as

product specifications.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

Extremely flammable aerosol. Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from strong acids and strong oxidizers.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. On burning: release of harmful/irritant gases/vapours. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Harmful in contact with skin.

Acute toxicity (inhalation) : Harmful if inhaled

Acute toxicity (inhalation)	Harmful if inhaled.
Air Intake & Carburettor Cleaner (Aerosol)	
ATE CLP (dermal)	1762,821 mg/kg bodyweight
ATE CLP (gases)	7692,308 ppmv/4h
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg Sprague-Dawley
LD50 dermal rabbit	> 15800 mg/kg New Zealand White
LC50 Inhalation - Rat	76 mg/l/4h Carworth Farms-Nelson
2-butoxyethanol (111-76-2)	
LD50 oral rat	1200 mg/kg bodyweight Rat
LD50 dermal rat	> 2000 mg/kg bodyweight Sprague-Dawley
LD50 dermal rabbit	24h 435 mg/kg New Zealand White
reaction mass of ethylbenzene and xylene	
LD50 oral rat	3523 mg/kg bodyweight F344/N
LD50 dermal rabbit	12126 mg/kg bodyweight New Zealand White
Skin corrosion/irritation :	Causes skin irritation.
Serious eye damage/irritation :	Causes serious eye irritation.
Respiratory or skin sensitisation :	Not classified
Germ cell mutagenicity :	Not classified
Carcinogenicity :	Not classified
Reproductive toxicity :	Not classified
STOT-single exposure :	May cause respiratory irritation.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

according to the NEACH Negulation (EC) 1907/2000 amended by Negulation (EO) 2020/070		
reaction mass of ethylbenzene and xylene		
STOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure	: May cause damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled, oral).	
reaction mass of ethylbenzene and xylene		
STOT-repeated exposure	May cause damage to organs (hearing organs) through prolonged or repeated exposure (oral, if inhaled).	
Aspiration hazard	: Not classified	
Air Intake & Carburettor Cleaner (Aerosol)		
Vaporizer	Aerosol	
Acetone (67-64-1)		
Viscosity, kinematic	0,342 mm²/s	
2-butoxyethanol (111-76-2)		
Viscosity, kinematic	< 3,7 mm²/s	
reaction mass of ethylbenzene and xylene		
Viscosity, kinematic	< 0,74 mm²/s	
Aliphatic, alicyclic or aromatic hydrocarbon	Yes	

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and

symptoms

: May have a narcotic effect at high concentrations

SECTION 12: Ecological information

12.1. Toxicity

: The product is not considered harmful to aquatic organisms nor to cause long-term adverse Ecology - general

effects in the environment.

: Not classified

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

(emeno)		
Acetone (67-64-1)		
LC50 - Fish [1]	96h 5540 mg/l oncorhynchus mykiss	
EC50 - Crustacea [1]	48h 7635 mg/l Daphnia cucullata	
NOEC chronic algae	8d 530 mg/l microcystis aeroginosa	
2-butoxyethanol (111-76-2)		
LC50 - Fish [1]	96h 1464 mg/l Oncorhynchus mykiss	
EC50 - Crustacea [1]	48h 1800 mg/l Daphnia magna	
EC50 - Other aquatic organisms [1]	72h 911 mg/l Pseudokirchneriella subcapitata	
NOEC (acute)	72h 88 mg/l Pseudokirchneriella subcapitata	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

reaction mass of ethylbenzene and xylene	
LC50 - Fish [1]	> 2,6 mg/l @96h
EC50 - Other aquatic organisms [1]	72h 2,2 mg/l

12.2. Persistence and degradability

Air Intake & Carburettor Cleaner (Aerosol)			
Persistence and degradability	This surfactant complies with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.		
Acetone (67-64-1)			
Persistence and degradability	Readily biodegradable.		
2-butoxyethanol (111-76-2)			
Persistence and degradability	Readily biodegradable.		

12.3. Bioaccumulative potential

Acetone (67-64-1)		
Bioaccumulative potential	Bioaccumulation unlikely.	
2-butoxyethanol (111-76-2)		
Bioaccumulative potential	Slightly bioaccumulative.	

12.4. Mobility in soil

Acetone (67-64-1)		
Ecology - soil Expected to be highly mobile in soil.		
2-butoxyethanol (111-76-2)		
Ecology - soil	Small adsorption.	

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations

: Container under pressure. Do not drill or burn even after use. Remove to an authorized waste treatment plant.

European List of Waste (LoW) code

15 01 10* - packaging containing residues of or contaminated by dangerous substances
 16 05 04* - gases in pressure containers (including halons) containing dangerous substances

17/06/2021 (Revision date) EN (English) 11/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	umber	1		
UN 1950	UN 1950	UN 1950	Not applicable	UN 1950
14.2. UN proper shipping	g name	,		1
AEROSOLS	Not applicable	Not applicable	Not applicable	Not applicable
Transport document descri	ption	,		1
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 , 2 (2.1)	UN 1950 , 2	Not applicable	UN 1950 , 2.1
14.3. Transport hazard c	lass(es)			
2.1	2 (2.1)	2	Not applicable	2.1
2	Not applicable	Not applicable	Not applicable	2
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards	,		1
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Not applicable	Dangerous for the environment: No

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 11
Transport category (ADR) : 2
Tunnel restriction code (ADR) : D

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

Not applicable

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Detergent Regulation (648/2004)

Labelling of contents		
Component	%	
aromatic hydrocarbons ≥30%		
aliphatic hydrocarbons	15-30%	

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name		Nomenclature	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

France

Occupational diseases			
Code	Description		
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide		

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Hydrocarbons, C3-4-rich, petroleum distillate is listed

SZW-lijst van mutagene stoffen : Hydrocarbons, C3-4-rich, petroleum distillate is listed SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – : None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

Switzerland

Storage class (LK) : LK 2 - Liquefied or pressurized gases

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUF	Full text of H- and EUH-statements:		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4		
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4		
Asp. Tox. 1	Aspiration hazard, Category 1		
EUH066	Repeated exposure may cause skin dryness or cracking.		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Gas 1A	Flammable gases, Category 1A		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
H220	Extremely flammable gas.		
H222	Extremely flammable aerosol.		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
H229	Pressurised container: May burst if heated.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H373	May cause damage to organs through prolonged or repeated exposure.	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.