# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

# WD-40® MULTI-USE PRODUCT - [Non-Aerosol]

# **1.2** Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Corrosion protection Grease Rust remover **Uses advised against:** No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

WD-40 Company Limited
 PO Box 440
 GB-Kiln Farm, Milton Keynes, MK11 3LF

Tel.: +44 (0) 1908 555400 Fax: +44 (0) 1908 266900 E-Mail: Compliance@wd40.co.uk Homepage: www.wd40.co.uk

WD-40 Company Limited Noorderpoort 93E NL- 5916PJ Venlo

Tel.: +31 85 487 46 91

WD-40 Company Limited, 252 Upper Third Street, Milton Keynes, MK9 1DZ +44 (0)1908 555450

M

Danka Import Export 548 St Joseph High Road SVR 1018 St Venera

Tel.: +356 21233649 Fax: +356 21233501 E-Mail: Danka@maltanet.net

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

# 1.4 Emergency telephone number Emergency information services / official advisory body:

Medicines & Poisons Info Office - Mater Dei Hospital, Msida MSD 2090, Malta - Tel.: +356 2545 6508 Emergency Ambulance - Tel.: 112 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 09.02.2023 PDF print date: 30.03.2023 WD-40® MULTI-USE PRODUCT - [Non-Aerosol]

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week) +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week) **Telephone number of the company in case of emergencies:** +44 20 3807 3798

#### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixtureClassification according to Regulation (EC) 1272/2008 (CLP)Hazard classHazard categoryHazard statementFlam. Liq.3H226-Flammable liquid and vapour.Asp. Tox.1H304-May be fatal if swallowed and enters airways.STOT SE3H336-May cause drowsiness or dizziness.

#### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H226-Flammable liquid and vapour. H304-May be fatal if swallowed and enters airways. H336-May cause drowsiness or dizziness.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P312-Call a POISON CENTRE / doctor if you feel unwell. P331-Do NOT induce vomiting.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

# **SECTION 3: Composition/information on ingredients**

3.1 Substancesn.a.3.2 Mixtures

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%	
aromatics	
Registration number (REACH)	01-2119463258-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	919-857-5
CAS	
content %	60-80
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH066
factors	Flam. Liq. 3, H226
	STOT SE 3, H336
	Asp. Tox. 1. H304

Free from:

CFC

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Respiratory arrest - Artificial respiration apparatus necessary.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water. Consult doctor immediately - keep Data Sheet available. Do not induce vomiting. Danger of aspiration. In case of vomiting, keep head low so that the stomach content does not reach the lungs.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur: Irritation of the eyes Inhalation: Headaches Nausea Dizziness Irritation of the respiratory tract Effects/damages the central nervous system With long-term contact: Dermatitis (skin inflammation) Ingestion: Nausea Vomiting Diarrhoea Danger of aspiration. Chemical pneumonitis (condition similar to pneumonia) (B) (R) (M)
Page 4 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 09.02.2023 / 0010
Replacing version dated / version: 26.09.2022 / 0009
Valid from: 09.02.2023
PDF print date: 30.03.2023
WD-40(B) MULTI-USE PRODUCT - [Non-Aerosol]

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. **4.3 Indication of any immediate medical attention and special treatment needed** n.c.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media Suitable extinguishing media Foam CO2 Extinction powder Water jet spray Unsuitable extinguishing media High volume water jet 5.2 Special hazards arising from the substance or mixture In case of fire the following can develop: Oxides of carbon Toxic pyrolysis products. Explosive vapour/air or gas/air mixtures. 5.3 Advice for firefighters For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke. Take measures against electrostatic charging, if appropriate. Avoid contact with eyes or skin. (B) (RL) (M) Page 5 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.02.2023 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 09.02.2023 PDF print date: 30.03.2023 WD-40® MULTI-USE PRODUCT - [Non-Aerosol] Do not carry cleaning cloths soaked in product in trouser pockets. Observe directions on label and instructions for use. Use working methods according to operating instructions. 7.1.2 Notes on general hygiene measures at the workplace General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed. 7.2 Conditions for safe storage, including any incompatibilities Keep out of access to unauthorised individuals. Not to be stored in gangways or stair wells. Store product closed and only in original packing. Do not store with flammable or self-igniting materials. Observe special storage conditions. Observe special storage conditions. Store in a dry place. Store cool. 7.3 Specific end use(s) No information available at present. Observe the instructions for good working practice and the recommendations for risk assessment. Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal). **SECTION 8: Exposure controls/personal protection** 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C	9-C11, n-alkanes, isoalkanes, cy	clics, <2% aromatics	
WEL-TWA: 800 mg/m3	-	WEL-STEL:		
Monitoring procedures:	-	Draeger - Hydrocarbons 0,1%/c	(81 03 571)	
	-	Draeger - Hydrocarbons 2/a (81	03 581)	
	-	Compur - KITA-187 S (551 174)	,	
BMGV:			Other information:	(OEL acc. to RCP-
			method, paragraphs	84-87, EH40)
Chemical Name	Hydrocarbons, C	9-C11, n-alkanes, isoalkanes, cy	clics, <2% aromatics	
OELV-8h: 100 ppm (573 mg/m3	3) ("Stoddard	OELV-15min:		
solvent", [White spirit])				
Monitoring procedures:	-	Draeger - Hydrocarbons 0,1%/c	(81 03 571)	
	-	Draeger - Hydrocarbons 2/a (81	03 581)	
	- (	Compur - KITA-187 S (551 174)	,	
BLV:			Other information:	
Chemical Name	Oil mist, mineral			
WEL-TWA: 5 mg/m3 (Mineral o	il, excluding	WEL-STEL:		
metal working fluids, ACGIH)	, C			
Monitoring procedures:	-	Draeger - Oil Mist 1/a (67 33 031	)	
BMGV:			Other information:	
Chemical Name	Oil mist, mineral			
OELV-8h: 5 mg/m3 (Mineral oil,	pure, highly &	OELV-15min:		
severely refined (inhalable))				
Monitoring procedures:	-	Draeger - Oil Mist 1/a (67 33 031	)	
BLV:			Other information:	
Chemical Name	Paraffin wax, furr	ie		
WEL-TWA: 2 mg/m3		WEL-STEL: 6 mg/m3		
Monitoring procedures:				
BMGV:			Other information:	
Chemical Name	Paraffin wax, furr	ne		
OELV-8h: 2 mg/m3		OELV-15min: 6 mg/m3		
Monitoring procedures:				
BLV:			Other information:	

Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	46	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	185	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	46	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	77	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	871	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |

OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU. (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BLV = Biological limit value |

Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average)

[9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |

OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period)

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

[8] = Short-term exposure limit value in relation to a reference period of 1 minute. (S.L.424.24), [9] = Inhalable fraction (S.L.424.24),
 [10] = Respirable fraction (S.L.424.24) |

BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Skin = Possibility of a significant uptake through the skin.

[11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. (S.L.424.24), [12] = The mist is defined as the thoracic fraction. (S.L.424.24), [13] = Established in accordance with the Annex to Directive 91/322/EEC. (S.L.424.24), [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques

(B) (M)
 Page 7 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 09.02.2023 / 0010
 Replacing version dated / version: 26.09.2022 / 0009
 Valid from: 09.02.2023
 PDF print date: 30.03.2023
 WD-40(B) MULTI-USE PRODUCT - [Non-Aerosol]

that complement the OELV. (S.L.424.24). (EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

#### 8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and nonmetrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: >= 0,4 Permeation time (penetration time) in minutes: >= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Melting point/freezing point: Liquid Amber Characteristic <-66 °C (ASTM D 97) (B) (RL) (M) Page 8 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.02.2023 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 09.02.2023 PDF print date: 30.03.2023 WD-40® MULTI-USE PRODUCT - [Non-Aerosol] 176 °C ((760 mmHg)) Boiling point or initial boiling point and boiling range: Flammability: Flammable Lower explosion limit: 0,6 Vol-% (Naphtha (petroleum), hydrotreated heavy) Upper explosion limit: 8,0 Vol-% (Naphtha (petroleum), hydrotreated heavy) Flash point: 47 °C (Tag, open cup) Auto-ignition temperature: There is no information available on this parameter. Decomposition temperature: There is no information available on this parameter. Mixture is non-soluble (in water). pH: Kinematic viscosity: <1 cSt Insoluble Solubility: Partition coefficient n-octanol/water (log value): Does not apply to mixtures. Vapour pressure: There is no information available on this parameter. Density and/or relative density: 0,817 g/ml (21°C) Relative vapour density: >1 Particle characteristics: Does not apply to liquids. 9.2 Other information Explosives: Possible build up of explosive/highly flammable vapour/air mixture. Product is not explosive. Oxidising liquids: There is no information available on this parameter.

#### **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** See also section 7. Heating, open flame, ignition sources **10.5 Incompatible materials** See also section 7. Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** See also section 5.2

No decomposition when used as directed.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

oxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	-					n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

				Tost mothod	Notes
•					Notes
		nig/kg		Oral Toxicity)	
LD50	>5000	mg/kg	Rabbit		
	. 10 E		Det		
LDOU	>10,5	mg/i/4n	Rai		
			Rabbit		Not irritant,
				Dermal	Repeated
				Irritation/Corrosion)	exposure may
					cause skin
					dryness or
					cracking.
					Repeated
					exposure may
					cause skin
					dryness or
			Dabbit		cracking. Not irritant
			Rabbit		NOT ITTEAT
			Guinea nia		No (skin
					contact)
			Salmonella		Negative,
				Reverse Mutation	Analogous
			-,		conclusion
			Human being		Negative,
			l i i i i i i i i i i i i i i i i i i i		Analogous
				Chromosome	conclusion
				Aberration Test)	
			Mouse	OECD 476 (In Vitro	Negative,
				Mammalian Cell Gene	Analogous
					conclusion
			Rat		Negative,
					Analogous
					conclusion
					Negative,
					Analogous
					conclusion
					Chinese
					hamster Negative,
					Analogous
					conclusion
NOAEC	1100	ma/m3	Mouse		Female
110/120	1100	ing/ine	modee		1 onnaio
NOAEC	>= 2200	mg/m3	Mouse	OECD 453	Male
				(Combined Chronic	
				Toxicity/Carcinogenicit	
				y Studies)	
NOAEL	>= 3000		Rat		Male
		bw/d		Generation	
NOAE	4500		D-1		E a sea d
NOAEL	>= 1500		Rat		Female
		D/Wa			
				Siddy)	Movies
					May cause drowsiness or
					nizzineee
					dizziness., STOT SE 3
					STOT SE 3, H336
	Endpoint LD50 LD50 	Endpoint         Value           LD50         >5000           LD50         >18,5           LD50         >18,5           ID50         >18,5           ID50         >18,5           ID50         >10,0           ID50         ID50           ID50         >10,0           ID50         ID50           ID50         ID50	LD50       >5000       mg/kg         LD50       >18,5       mg/l/4h         LD50       >18,5       mg/l/4h         IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	EndpointValueUnitOrganismLD50>5000mg/kgRatLD50>5000mg/kgRabbitLD50>18,5mg/l/4hRatLD50>18,5mg/l/4hRatLD50>18,5mg/l/4hRatLD50>18,5mg/l/4hRatLD50>18,5mg/l/4hRatLD50>18,5mg/l/4hRatLD50>18,5mg/l/4hRatLD50>18,5mg/l/4hRatLD50>18,5mg/l/4hRatLD50IIILD50IIILD50IIILD50IIILD50IMouseILD50mg/m3MouseNOAEL>= 3000mg/kgRatNOAEL>= 1500mg/kgRat	EndpointValueUnitOrganismTest methodLD50>5000mg/kgRatOECD 401 (Acute OFECD 402 (Acute) Dermal Toxicity)LD50>5000mg/kgRabbitOECD 403 (Acute Dermal Toxicity)LD50>18.5mg/l/4hRatOECD 403 (Acute Inhalation Toxicity)LD50>18.5mg/l/4hRatOECD 403 (Acute Inhalation Toxicity)LD50>18.5mg/l/4hRatOECD 403 (Acute Inhalation Toxicity)LD50>18.5mg/l/4hRatOECD 404 (Acute Dermal Irritation/Corrosion)LD51LD51LD51RabbitOECD 405 (Acute Eye Irritation/Corrosion)LD51LD51LD51LD51CECD 405 (Acute Eye Irritation/Corrosion)LD51LD51LD51LD51CECD 405 (Acute Eye Irritation/Corrosion)LD51LD51LD51LD51CECD 476 (Koute Eye Irritation/Corrosion)LD51LD51LD51Salmonella typhimurium Test)OECD 473 (In Vitro Marmalian Chromsome Aberration Test)LD51LD51LD51RatOECD 473 (In Vitro Marmalian Cell Gene Mutation Test)LD51LD51LD51RatOECD 479 (Genetic Toxicology - Notino 

Symptoms:						unconsciousnes s, headaches, dizziness, discoloration of the skin, vomiting, diarrhoea
Specific target organ toxicity - repeated exposure (STOT-	NOAEL	3000	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral	Analogous conclusion
RE), oral:					Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-	NOAEC	1444	ppm	Rat	OECD 413 (Subchronic Inhalation	Analogous conclusion
RE), inhalat.:					Toxicity - 90-Day Study)	

# 11.2. Information on other hazards

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting						Does not apply
properties:						to mixtures.
Other information:						No other relevant information available on adverse effects on health.

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

WD-40® MULTI-USE PRODUCT - [Non-Aerosol]								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:							n.d.a.	
12.1. Toxicity to							n.d.a.	
daphnia:								
12.1. Toxicity to algae:							n.d.a.	
12.2. Persistence and							n.d.a.	
degradability:								
12.3. Bioaccumulative							n.d.a.	
potential:								
12.4. Mobility in soil:							n.d.a.	
12.5. Results of PBT							n.d.a.	
and vPvB assessment								
12.6. Endocrine							Does not apply	
disrupting properties:							to mixtures.	
12.7. Other adverse							No information	
effects:							available on	
							other adverse	
							effects on the	
							environment.	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,13	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

(B) (M)
 Page 11 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 09.02.2023 / 0010
 Replacing version dated / version: 26.09.2022 / 0009
 Valid from: 09.02.2023
 PDF print date: 30.03.2023
 WD-40(B) MULTI-USE PRODUCT - [Non-Aerosol]

12.1. Toxicity to algae:	ErC50	72h	>1000	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	EbC50	72h	>1000	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	100	mg/l	Raphidocelis	OECD 201	
					subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	3	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.2. Persistence and		28d	80	%		OECD 301 F	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry	
						Test)	
12.3. Bioaccumulative			5-6,7				High
potential:							
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Toxicity to bacteria:	EL50	48h	0,95	mg/l			QSAR

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

14 06 03 other solvents and solvent mixtures

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

# E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

15 01 04 metallic packaging

15 01 01 paper and cardboard packaging

Dispose using dual system.

#### **SECTION 14: Transport information**

General statements		
Transport by road/by rail (ADR/RID)		
14.1. UN number or ID number:	3295	
14.2. UN proper shipping name:		
UN 3295 HYDROCARBONS, LIQUID, N.O.S.		
14.3. Transport hazard class(es):	3	
14.4. Packing group:	III	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	D/E	
Classification code:	F1	
LQ:	5 L	
Transport category:	3	
Transport by sea (IMDG-code)		
14.1. UN number or ID number:	3295	
14.2. UN proper shipping name:		
UN 3295 HYDROCARBONS, LIQUID, N.O.S.		

- <sup>6</sup> 8 R M		
Page 12 of 14		
Safety data sheet according to Regulation (EC) No 1907	/2006, Annex II	
Revision date / version: 09.02.2023 / 0010		
Replacing version dated / version: 26.09.2022 / 0009		
Valid from: 09.02.2023		
PDF print date: 30.03.2023		
WD-40® MULTI-USE PRODUCT - [Non-Aerosol]		
14.3. Transport hazard class(es):	3	
14.4. Packing group:	III	
14.5. Environmental hazards:	Not applicable	
Marine Pollutant:	Not applicable	
EmS:	F-E, S-D	
Transport by air (IATA)		
14.1. UN number or ID number:	3295	
14.2. UN proper shipping name:		
UN 3295 Hydrocarbons, liquid, n.o.s.		
14.3. Transport hazard class(es):	3	
14.4. Packing group:	III	
14.5. Environmental hazards:	Not applicable	
14.6. Special precautions for user		
Persons employed in transporting dangerous goods mus		
All persons involved in transporting must observe safety	regulations.	
Precautions must be taken to prevent damage.		
14.7. Maritime transport in bulk according	to IMO instruments	
Freighted as packaged goods rather than in bulk, therefo		
Minimum amount regulations have not been taken into a	ccount.	
Danger code and packing code on request.		
Comply with special provisions.		

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**SECTION 15: Regulatory information** 

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for	referred to in Article 3(10) for
		the application of - Lower-tier	the application of - Upper-tier
		requirements	requirements
P5c		5000	50000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

~ 67,2 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

#### **15.2 Chemical safety assessment**

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

1-16

#### EUF0003

**Revised sections:** 

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

#### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 3, H226	Classification based on test data.
Asp. Tox. 1, H304	Classification according to calculation procedure.

STOT SE 3, H336

Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Flam. Liq. — Flammable liquid

Asp. Tox. — Aspiration hazard STOT SE — Specific target organ toxicity - single exposure - narcotic effects

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

**GESTIS** Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

#### Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council bw body weight CAS Chemical Abstracts Service Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of CLP substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon drv weight dw for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) EC European Community ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community **EINECS** European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances European Norms FN United States Environmental Protection Agency (United States of America) EPA  $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera etc. EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number

© RI M Page 14 of 14 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.02.2023 / 0010 Replacing version dated / version: 26.09.2022 / 0009 Valid from: 09.02.2023 PDF print date: 30.03.2023 WD-40® MULTI-USE PRODUCT - [Non-Aerosol] general gen. ĞHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc Kow octanol-water partition coefficient IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. **IUCLIDInternational Uniform Chemical Information Database** IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient Limited Quantities LQ MARPOL International Convention for the Prevention of Marine Pollution from Ships n.a. not applicable n.av. not available not checked n.c. n.d.a. no data available NIOSHNational Institute for Occupational Safety and Health (USA) No-longer-Polymer NLP NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic PE Polyethylene PNEC Predicted No Effect Concentration ppm parts per million PVC Polyvinylchloride Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning REACH the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical REACH-IT List-No. identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the RID International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.